

TWT BYPASS TREATMENT SYSTEMS (custom quote only)

See Section A-8 of catalog (home page) for Additional Technical Information

ITEM NUMBER & PRODUCT DESCRIPTION:	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
---------------------------------------	-----------------------	-----------------------

TWT-BP-RC-2

Factory assembled 2-inch pipe solenoid and recirculating pump for use with recirculating water systems. Designed to treat up to 4,800 gallons per hour
This unit is Floor Mounted [w/Ionization]

*

TBD

TWT-BP-RC-4

Factory assembled 4-inch pipe solenoid and recirculating pump for use with recirculating water systems. Designed to treat up to 19,000 gallons per hour
This unit is Floor Mounted

*


TBD

TWT-BP-RC-6

Factory assembled 6-inch pipe solenoid and recirculating pump for use with recirculating water systems. Designed to treat up to 43,000 gallons per hour
This unit is Floor Mounted

*

TBD



*Custom built according to customer system application and ByPass GPM requirements.
 Size and weight to be determined at time of purchase

*Custom System Quote: Industry specific fluid treatment needs and up grades

Custom Installation: Pricing to be established based upon proposal submitted at time of sale based on materials cost at time of purchase

Note: Above systems are fully integrated and factory assembled and mounted, offering end to end fluid management and treatment solutions

TBD: Carriers shipping and handling costs for products are constantly changing. For that reason, it is difficult for TWT to determine the exact shipping method and weight for products before TWT has a confirmed and accepted purchase order in-house.

TWT BRS-BACTERIAL REDUCTION SYSTEM

See Section A-8 of catalog (home page) for Additional Technical Information

Technologically Advanced Fluid Treatment Methods for the Meat, Poultry and Related Processing Industries – For any Industry Requiring High Volume Bacterial Reduction

ITEM NUMBER & PRODUCT DESCRIPTION:	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
---------------------------------------	-----------------------	-----------------------

TWT-BRS-73
TWT-BRS73 Central System for Multiple Injector Lines • Four Stage Filtration • Two Stage Deposit Control Technology • Triple Quattrra 100 UV Disinfection & Purification
(System Treatment Up To 1500 GPH)



Four stage filtration configured to remove particulate matter that may inhibit the effectiveness of the UV system.



Triple Quattrra 100 UV system configured to provide more exposure to the UV light, ensuring a higher kill rate of the bacteria.



Post filtration

Though similar in appearance the system component configuration is assembled according to treatment and application requirements

TWT-BRS-2
TWT-BRS/2 Central System for Multiple Injector Lines • Two Stage Filtration • Deposit Control Technology • Dual Quattrra 50 UV Disinfection & Purification
(System Treatment Up To 1500 GPH)



Two stage filtration configured to remove particulate matter that may inhibit the effectiveness of the UV system.



Dual Quattrra 50 UV system configured to provide more exposure to the UV light, ensuring a higher kill rate of the bacteria.



Custom System Quote:Industry specific fluid treatment needs and up grades
Custom Installation:Pricing to be established based upon proposal submitted at time of sale based on materials cost at time of purchase
Note: Above systems are fully integrated and factory assembled and mounted, offering end to endfluid management and treatment solutions
*Custom built, size to be determined at at time of purchase

TWT BRS–BACTERIAL REDUCTION SYSTEMS

See Section A-11 of catalog (home page) for Additional Technical Information

Technologically Advanced Fluid Treatment Methods for the Meat, Poultry and Related Processing Industries – For any Industry Requiring High Volume Bacterial Reduction

ITEM NUMBER & PRODUCT DESCRIPTION:	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
TWT-BRS-1 Though similar in exterior design to the BRS3 component configuration is different TWT-BRS/1 Central System for Multiple Injector Applications (Refrigerated) Filtration • Deposit Control Technology • Ozone & UV Disinfection/Purification (System Treatment Up To 3000 GPH)	144"L x 85"H x 76"D	TBD

Though similar in appearance the system component configuration is assembled according to treatment and application requirements



TWT-BRS-3 TWT-BRS/3 Central System for Multiple Injector Applications (Refrigerated) Filtration • Deposit Control Technology UV Disinfection & Purification (System Treatment Up To 3000 GPH)	144"L x 85"H x 76"D	TBD
---	---------------------	-----

Custom System Quote:Industry specific fluid treatment needs and up grades
Custom Installation:Pricing to be established based upon proposal submitted at time of sale based on materials cost at time of purchase
Note: Above systems are fully integrated and factory assembled and mounted, offering end to endfluid management and treatment solutions
***Custom built, size to be determined at at time of purchase**
TBD: Carriers shipping and handling costs for products are constantly changing. For that reason, it is difficult for TWT to determine the exact shipping method and weight for products before TWT has a confirmed and accepted purchase order in-house.

TWT BRS–BACTERIAL REDUCTION SYSTEMS

See Section A-11 of catalog (home page) for Additional Technical Information

Technologically Advanced Fluid Treatment Methods for the Meat, Poultry and Related Processing Industries – For any Industry Requiring High Volume Bacterial Reduction

**ITEM NUMBER &
PRODUCT DESCRIPTION:**

**PRODUCT
DIMENSIONS**

**APPROX SHIP
WEIGHT**

TWT-BRS-4

TWT-BRS/4 Point-Of-Use Single Injection Application

- Filtration • Deposit Control Technology
 - UV Disinfection & Purification
- (System Treatment Up To 1000 GPM)

64"W x 50"H x 20"D **TBD**



TWT-BRS-9

TWT-BRS/9 Point-Of-Use Fluid Treatment & Conditioning • Deposit Control Technology

- UV Disinfection & Purification


50 GPM System

*

TBD

**Custom Built and Assembled According to
Treatment and Application Requirements**

See section A-11 in catalog for additional information



*Custom built according to customer specifications.
Size and weight to be determined at time of purchase

TWT-BRS-10

TWT-BRS/10 Point-Of-Use Fluid Treatment & Conditioning • Deposit Control Technology

- UV Disinfection & Purification


220 GPM System

*

TBD

**Custom Built and Assembled According to
Treatment and Application Requirements**

See section A-11 in catalog for additional information



*Custom built according to customer specifications.
Size and weight to be determined at time of purchase

Custom System Quote: Industry specific fluid treatment needs and up grades

Custom Installation: Pricing to be established based upon proposal submitted at time of sale based on materials cost at time of purchase

Note: Above systems are fully integrated and factory assembled and mounted, offering end to end fluid management and treatment solutions

TBD: Carriers shipping and handling costs for products are constantly changing. For that reason, it is difficult for TWT to determine the exact shipping method and weight for products before TWT has a confirmed and accepted purchase order in-house.

ALL-IN-ONE MD INTEGRATED WATER TREATMENT & CONDITIONING SYSTEMS P.O.E./P.O.U.

Filtration • Deposit Control • UV Disinfection/Purification

See Section A-10 of catalog (home page) for Additional Technical Information

ITEM NUMBER & PRODUCT DESCRIPTION:	GPM	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
---------------------------------------	-----	-----------------------	-----------------------

TWT-MD-1001 Mobile Home/Office treatment System Provides 4 Stages of Cleaning	2 GPM	30"W x 30"H x 10"D	40 lbs
---	-------	--------------------	--------

- Wall Mounted Water Treatment System • 2-Stage Filtration
- TWT® Deposit Control Technology • Ultra Violet Disinfection & Purification

Piping: 1/2" In/Out of system*Upgrades:* Customized TWT® systems to meet your treatment applications available upon request

TWT-MD-1002 Whole House/Office treatment System Provides 5 Stages of Cleaning	4 GPM	34"W x 30"H x 10"D	85 lbs
---	-------	--------------------	--------

- Wall Mounted Water Treatment System • 3-Stage Filtration
- TWT® Deposit Control Technology • Ultra Violet Disinfection & Purification

Piping: 3/4" In/Out of system*Upgrades:* Customized TWT® systems to meet your treatment applications available upon request

TWT-MD-1003 Whole House/Office treatment System Provides 5 Stages of Cleaning	8 GPM	49"W x 42"H x 15"D	170 lbs
---	-------	--------------------	---------

- Wall Mounted Water Treatment System • 3-Stage Filtration
- TWT® Deposit Control Technology • Ultra Violet Disinfection & Purification

Piping: 3/4" In/Out of system*Upgrades:* Customized TWT® systems to meet your treatment applications available upon request

TWT-MD-1004 Whole House/Office treatment System Provides 5 Stages of Cleaning	12 GPM	49"W x 42"H x 15"D	240 lbs
---	--------	--------------------	---------

- Wall Mounted Water Treatment System • 3-Stage Filtration
- TWT® Deposit Control Technology • Ultra Violet Disinfection & Purification

Piping: 1" In/Out of system

TWT Inc. recommends that an initial supply of replacement products e.g., replacement filters, UV lamps etc. be stored at owners facility at all times, that will insure uninterrupted service and treatment.

*Review product list for replacement filters and ultra-violet lamps.**Upgrades:* Customized TWT® systems to meet your treatment applications available upon request

ALL-IN-ONE MD INTEGRATED WATER TREATMENT & CONDITIONING SYSTEMS P.O.E./P.O.U.

Filtration • Deposit Control • UV Disinfection/Purification

See Section A-10 of catalog (home page) for Additional Technical Information

ITEM NUMBER & PRODUCT DESCRIPTION:	GPM	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
---------------------------------------	-----	-----------------------	-----------------------

TWT-MD-1005	15 GPM	49"W x 42"H x 15"D	240 lbs
--------------------	--------	--------------------	---------

Whole House/Office treatment System Provides 5 Stages of Cleaning

- Wall Mounted Water Treatment System • 3-Stage Filtration
- TWT® Deposit Control Technology • Ultra Violet Disinfection & Purification

Piping: 1" In/Out of system

TWT-MD-1006	30 GPM	52"W x 57"H x 16"D	246 lbs
--------------------	--------	--------------------	---------

Whole House/Office treatment System Provides 5 Stages of Cleaning

- Wall Mounted Water Treatment System • 3-Stage Filtration
- TWT® Deposit Control Technology • Ultra Violet Disinfection & Purification


Piping: 1 1/2" In/Out of system

TWT-SMD-1007*	50 GPM	80" W x 60"H x 32"D	** lbs
----------------------	--------	---------------------	--------

Compact, Self-Contained, Skid-Mounted Fluid Management System

- 2-Stage Filtration • TWT® Deposit Control Technology
- Ultra Violet Disinfection & Purification

Two UV Lamps Required

Piping: 2" In/Out of system

TWT-SMD-1007+1*	50 GPM	68" W x 52"H x 30"D	** lbs
------------------------	--------	---------------------	--------

Compact, Self-Contained, Skid-Mounted Fluid Management System

- 3-Stage Filtration • TWT® Deposit Control Technology
- Ultra Violet Disinfection & Purification

Two UV Lamps Required

Piping: 2" In/Out of system

*TWT-SMD-series upgrades for larger GPM requirements are available upon request

**TBD (may vary according component assembly)

Custom Orders: Larger pipe size (GPM) applications available upon request

TWT Inc. recommends that an initial supply of replacement products e.g., replacement filters, UV lamps etc. be stored at owners facility at all times, that will insure uninterrupted service and treatment.

Review product list for replacement filters and ultra-violet lamps.

ALL-IN-ONE MD INTEGRATED WATER TREATMENT & CONDITIONING SYSTEMS P.O.E/P.O.U.

Filtration • Deposit Control • UV Disinfection/Purification

See Section A-10 of catalog (home page) for Additional Technical Information

ITEM NUMBER & PRODUCT DESCRIPTION:	GPM	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
---------------------------------------	-----	-----------------------	-----------------------

TWT-SMD-1007+2*	50 GPM	80" W x 52"H x 32"D	** lbs
------------------------	--------	---------------------	--------

Compact, Self-Contained, Skid-Mounted Fluid Management System

- 4-Stage Filtration • TWT® Deposit Control Technology
- Ultra Violet Disinfection & Purification

Two UV Lamps Required

Piping: 2" In/Out of system

TWT-SMD-1008*	100 GPM	72" W x 52"H x 34"D	** lbs
----------------------	---------	---------------------	--------

Compact, Self-Contained, Skid-Mounted Fluid Management System

- 2-Stage Filtration • TWT® Deposit Control Technology
- Ultra Violet Disinfection & Purification

Four UV Lamps Required

Piping: 2" In/Out of system

TWT-SMD-1008+1*	100 GPM	80" W x 60"H x 34"D	** lbs
------------------------	---------	---------------------	--------

Compact, Self-Contained, Skid-Mounted Fluid Management System

- 3-Stage Filtration • TWT® Deposit Control Technology
- Ultra Violet Disinfection & Purification

Four UV Lamps Required

Piping: 2" In/Out of system

*TWT-SMD-series upgrades for larger GPM requirements are available upon request

**TBD (may vary according component assembly)

Custom Orders: Larger pipe size (GPM) applications available upon request

TWT Inc. recommends that an initial supply of replacement products e.g., replacement filters, UV lamps etc. be stored at owners facility at all times, that will insure uninterrupted service and treatment.

Review product list for replacement filters and ultra-violet lamps.

ALL-IN-ONE MD INTEGRATED WATER TREATMENT & CONDITIONING SYSTEMS P.O.E./P.O.U.

Filtration • Deposit Control • UV Disinfection/Purification

See Section A-10 of catalog (home page) for Additional Technical Information

ITEM NUMBER & PRODUCT DESCRIPTION:	GPM	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
---------------------------------------	-----	-----------------------	-----------------------

TWT-SMD-1008+2* Compact, Self-Contained, Skid-Mounted Fluid Management System	100 GPM	80" W x 52"H x 34"D	** lbs
---	---------	---------------------	--------

- 4-Stage Filtration • TWT® Deposit Control Technology
- Ultra Violet Disinfection & Purification

Four UV Lamps Required

Piping: 2" In/Out of system



TWT-SMD-200+4 Compact, Self-Contained, Skid-Mounted Fluid Management System	200 GPM	84"W X 72"H X 60"D	*800 lbs
---	---------	--------------------	----------

- 4-Filter Housings • Stage Filtration • TWT® Deposit Control Technology
- Ultra Violet Disinfection & Purification

Seven UV Lamps Required

Piping: 3" In/Out of system



*TWT-SMD-series upgrades for larger GPM requirements are available upon request

**TBD (may vary according component assembly)

Custom Orders: Larger pipe size (GPM) applications available upon request

TWT Inc. recommends that an initial supply of replacement products e.g., replacement filters, UV lamps etc.

be stored at owners facility at all times, that will insure uninterrupted service and treatment.

Review product list for replacement filters and ultra-violet lamps.



REPLACEMENT FILTRATION PRODUCTS/MD SERIES—Based on Water Treatment Requirements

See Section A-10 of catalog (home page) for Additional Technical Information

ITEM NUMBER & PRODUCT DESCRIPTION:	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
TWT-MD-1001-RF Set of 2 filters—1 Sediment, 1 GAC	15" x 4 1/2" x 6 1/2"	8 lbs
TWT-MD-1002-RF Set of 3 filters—1 Sediment, 1 GAC, 1 Carbon Block	25 1/2" x 6 1/2" x 5 1/2"	11 lbs
TWT-MD-1003-RF Set of 3 filters—1 Sediment, 1 GAC, 1 Carbon Block	25 1/2" x 6 1/2" x 5 1/2"	11 lbs
TWT-MD-1004-RF Set of 3 filters—1 Sediment, 1 GAC, 1 Carbon Block	25 1/2" x 6 1/2" x 5 1/2"	20 lbs
TWT-MD-1005-RF Set of 3 filters—1 Sediment, 1 GAC, 1 Carbon Block	25 1/2" x 6 1/2" x 5 1/2"	20 lbs
TWT-MD-1006-RF Set of 3 filters—1 Sediment, 1 GAC, 1 Carbon Block	25 1/2" x 6 1/2" x 5 1/2"	20 lbs
TWT-SMD-1007-RF Set of 2 filters—1 Sediment, 1 Carbon Block		
TWT-SMD-1008-RF Set of 2 filters—1 Sediment, 1 Carbon Block		

REPLACEMENT FILTRATION PRODUCTS/MD SERIES—Based on Water Treatment Requirements

TWT-MD-1001-RF1 Set of 2 filters—1 Sediment, 1 Carbon Block	15" x 4 1/2" x 6 1/2"	8 lbs
TWT-MD-1002-RF2* Set of 3 filters—1 Sediment, 2 Carbon Block	25 1/2" x 6 1/2" x 5 1/2"	11 lbs
TWT-MD-1003-RF2 Set of 3 filters—1 Sediment, 2 Carbon Block	25 1/2" x 6 1/2" x 5 1/2"	11 lbs
TWT-MD-1004-RF2 Set of 3 filters—1 Sediment, 2 Carbon Block	25 1/2" x 6 1/2" x 5 1/2"	20 lbs
TWT-MD-1005-RF2 Set of 3 filters—1 Sediment, 2 Carbon Block	25 1/2" x 6 1/2" x 5 1/2"	20 lbs
TWT-MD-1006-RF2 Set of 3 filters—1 Sediment, 2 Carbon Block	25 1/2" x 6 1/2" x 5 1/2"	20 lbs

Filters are interchangeable allowing you to meet your specific water treatment needs at all times.

Sediment: Sediment reduction/removal

GAC: Granulated activated carbon for taste, odor, organic chemicals and chlorine reduction/removal.

GAC/KDF-55: Granulated activated carbon with KDF-55, specially formulated copper/zinc alloy media designed to remove chlorine, lead, volatile organic chemicals, hydrogen sulfide, sulfur, herbicides, pesticides, chemical fertilizer residues and trihalomethanes

TWT recommends that filters be purchased in sets of two in order to ensure uninterrupted fluid treatment



*Denote 2 Carbon Block Filters

TWT ALL-IN-ONE DP INTEGRATED WATER TREATMENT & CONDITIONING SYSTEMS P.O.U./P.O.E.

Deposit Control • UV Disinfection Purification System—If Water Conditions Do Not Require Filtration


See Section A-10 of catalog (home page) for Additional Technical Information

ITEM NUMBER & PRODUCT DESCRIPTION:	GPM	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
TWT-DP-01	2 GPM	30"W x 30"H x 10"D	28 lbs
Integrated Fluid treatment System with High Intensity UV Light Kills 99.9° of all Bacteria Features TWT® Deposit Control Technology with Ultra Violet Disinfection & Purification			
<i>Piping:</i> 1/2" In/Out of system			

TWT-DP-02	4 GPM	34"W x 30"H x 10"D	77 lbs
Integrated Fluid treatment System with High Intensity UV Light Kills 99.9° of all Bacteria Features TWT® Deposit Control Technology with Ultra Violet Disinfection & Purification			
<i>Piping:</i> 3/4" In/Out of system			

TWT-DP-03	8 GPM	49"W x 42"H x 15"D	160 lbs
Integrated Fluid treatment System with High Intensity UV Light Kills 99.9° of all Bacteria Features TWT® Deposit Control Technology with Ultra Violet Disinfection & Purification			
<i>Piping:</i> 3/4" In/Out of system			

TWT-DP-04	12 GPM	49"W x 42"H x 15"D	180 lbs
Integrated Fluid treatment System with High Intensity UV Light Kills 99.9° of all Bacteria. Features TWT® Deposit Control Technology with Ultra Violet Disinfection & Purification.			
<i>Piping:</i> 1" In/Out of system			



The TWT-DP series product line is similar in design and appearance. Weight, size and component assembly will differ based on GPM treatment requirements.

Custom Orders: Larger pipe size (GPM) applications available upon request

TWT Inc. recommends that an initial supply of replacement products e.g., replacement filters, UV lamps etc. be stored at owners facility at all times, that will insure uninterrupted service and treatment. Review product list for filters and ultra-violet lamps.

Upgrades: Customized TWT® systems to meet your treatment applications available upon request

TWT ALL-IN-ONE DP INTEGRATED WATER TREATMENT & CONDITIONING SYSTEMS P.O.U./P.O.E.

Deposit Control • UV Disinfection Purification System

See Section A-10 of catalog (home page) for Additional Technical Information

ITEM NUMBER & PRODUCT DESCRIPTION:	GPM	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
---------------------------------------	-----	-----------------------	-----------------------

TWT-DP-05	15 GPM	49"W x 42"H x 15"D	180 lbs
------------------	--------	--------------------	---------

Integrated Fluid treatment System with High Intensity UV Light
Kills 99.9° of all Bacteria*Piping:* 1" In/Out of systemFeatures TWT® Deposit Control Technology with
Ultra Violet Disinfection & Purification.

TWT-DP-06	30 GPM	52"W x 57"H x 15"D	185 lbs
------------------	--------	--------------------	---------

Integrated Fluid treatment System with High Intensity UV Light
Kills 99.9° of all Bacteria*Piping:* 1.5" In/Out of systemFeatures TWT® Deposit Control Technology with
Ultra Violet Disinfection & Purification.

TWT-DP-07	50 GPM	44"W x 58"H x 14"D	229 lbs
------------------	--------	--------------------	---------

Integrated Fluid treatment System with High Intensity UV Light
Kills 99.9° of all Bacteria*Piping:* 2" In/Out of systemFeatures TWT® Deposit Control Technology with
Ultra Violet Disinfection & Purification.

Two UV Lamps Required

TWT-DP-08	100 GPM	44"W x 58"H x 14"D	235 lbs
------------------	---------	--------------------	---------

Integrated Fluid treatment System with High Intensity UV Light
Kills 99.9° of all Bacteria*Piping:* 2" In/Out of systemFeatures TWT® Deposit Control
Technology with Ultra Violet Disinfection
& Purification.

Two UV Lamps Required

The TWT-DP series product line is similar
in design and appearance. Weight, size
and component assembly will differ based
on GPM treatment requirements.**Custom Orders:** Larger pipe size (GPM) applications available upon request**TWT Inc. recommends that an initial supply of replacement products e.g., replacement filters, UV lamps etc. be stored at owners facility at all times, that will insure uninterrupted service and treatment. Review product list for replacement filters and ultra-violet lamps.****Upgrades:** Customized TWT® systems to meet your treatment applications available upon request

ACCESSORIES FOR ABOVE MD/DP TREATMENT SYSTEMS P.O.U. / P.O.E.

Stainless Steel Frame Supports for Free Standing Installation – Two Per Unit Required


See Section A-10 of catalog (home page) for Additional Technical Information

ITEM NUMBER & PRODUCT DESCRIPTION:	GPM	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
---------------------------------------	-----	-----------------------	-----------------------

TWT-MD/DP-2FS

Sized according to system

*



*Custom built according to customer specifications.
Size and weight to be determined at time of purchase

TWT- SOLAR POWERED TRANSPORTABLE WATER TREATMENT SYSTEM

Filtration • Deposit Control • UV Disinfection/Purification

ITEM NUMBER & PRODUCT DESCRIPTION:	GPM	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
---------------------------------------	-----	-----------------------	-----------------------

TWT-SP-250-4

4 GPM

32"W X 30"D X 55"H

250 lbs.

Our Transportable Solar System Combines High-Quality Pre-Filtration with our Hi-power Ultra Violet Purification Technology to Produce a Complete water Quality System



TWT-SP-250-4

DISCOUNTS: Available upon request for volume
purchasers on a case by case basis


TWT-SP-1003

8 GPM

Custom Design

Solar Powered Transportable Water Management Treatment System
with 3-stage Filtration, TWT® Deposit Control Technology and
Ultra Violet Disinfection & Purification

*



TWT-SP-1003

*Custom built according to customer specifications.
Size and weight to be determined at time of purchase

TWT Inc. recommends that an initial supply of replacement products e.g., replacement filters, UV lamps etc. be stored at owners facility at all times, that will insure uninterrupted service and treatment. Review product list for replacement filters and ultra-violet lamps.

Upgrades: Customized TWT® systems to meet your treatment applications available upon request

TWT POINT-OF-USE WATER TREATMENT & CONDITIONING SYSTEM

Filtration • Deposit Control • UV Disinfection Purification System

See Section A-10 of catalog (home page) for Additional Technical Information

ITEM NUMBER & PRODUCT DESCRIPTION:	GPM	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
---------------------------------------	-----	-----------------------	-----------------------

TWT-RPOU001 Control Scale Deposits/Bacteria Corrosion, Algae, Colloids in your Water-Fed System Combines 2-Stage Filtration and TWT® Deposit Control Technology and Ultra Violet Disinfection & Purification to eliminate the bio-film that serves as a breeding ground for disease causing bacteria, collecting in your pipes, tubing and equipment. For pipe size applications 3/8" or less	1 GPM	13"W x 15 1/4" x 5 3/8"D	10 lb
---	-------	--------------------------	-------



TWT Inc. recommends that an initial supply of replacement products e.g., replacement filters, UV lamps etc. be stored at owners facility at all times, that will insure uninterrupted service and treatment. Review product list for replacement filters and ultra-violet lamps.

TWT-RPOU002 Control Scale Deposits/Bacteria Corrosion, Algae, Colloids in your Water-Fed System Combines 3-Stage Filtration and TWT® Deposit Control Technology and Ultra Violet Disinfection & Purification to eliminate the bio-film that serves as a breeding ground for disease causing bacteria, collecting in your pipes, tubing and equipment. For pipe size applications 3/8" or less	4 GPM	23"W x 15"H x 5 3/8"D	18 lbs
--	-------	-----------------------	--------



TWT Inc. recommends that an initial supply of replacement products e.g., replacement filters, UV lamps etc. be stored at owners facility at all times, that will insure uninterrupted service and treatment. Review product list for replacement filters and ultra-violet lamps.

TWT P.O.U. / P.O.E. WATER TREATMENT & CONDITIONING SYSTEM

Filtration • TWT Deposit Control Technology

TWT-POUS-300 3 Stage Filtration: Sediment, Resin, Carbon For pipe size applications 3/4" or less	1-2 GPM	27 1/2"W x 20"H x 10"D	*40 lbs
---	---------	------------------------	---------

TWT-POUE-400 3 Stage Filtration: Sediment, Carbon, GAC/KDF or pipe size applications 3/4" or less	1-2 GPM	27 1/2"W x 20"H x 10"D	*40 lbs
--	---------	------------------------	---------

TWT® the Ultimate in Water Treatment & Conditioning
Technologically Advanced Fluid Treatment Method for
P.O.U./P.O.E. Applications
Multi-Stage Filtration, Electro-Magnetic Fluid Conditioning and
Flow Meter Combined for Maximum Effectiveness

TWT Inc. recommends that an initial supply of replacement products e.g., replacement filters be stored at owners facility at all times, that will insure uninterrupted service and treatment. Review product list for replacement filters (See page 61 for replacement filters).

DISCOUNTS: Available upon request for volume purchasers on a case by case basis

* Will vary based on filters used



TWT POINT-OF-USE WATER TREATMENT & CONDITIONING SYSTEM


Filtration • Optional Water Softening • Deposit Control • UV Disinfection Purification System

See Section A-10 of catalog (home page) for Additional Technical Information

ITEM NUMBER & PRODUCT DESCRIPTION:	GPM	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
TWT-POEPOUV-600	1-2 GPM	26"W x 24" H x 10"D	50 lbs (will vary based on filters used)
Control Scale Deposits/Bacteria Corrosion, Algae, Colloids in your Water-Fed System For pipe size applications 3/4" or less			

*Filters are interchangeable allowing you to meet your specific water treatment needs at all times.**Filters preference must specified upon placement of purchase order*

1. Sediment 5-10 Micron: Pleated Washable and reusable for sediment reduction/removal
2. Resin Filter: Water softening resin filter
3. GAC: Granulated activated carbon for taste, odor, organic chemicals and chlorine reduction/removal.
4. GAC/KDF-55: Granulated activated carbon with KDF-55, specially formulated copper/zinc alloy media designed to remove chlorine, lead, volatile organic chemicals, hydrogen sulfide, sulfur, herbicides, pesticides, chemical fertilizer residues and trihalomethanes

**TOTAL WATER CONTROL SYSTEMS (TWCS) For Industrial, Cooling Towers, and Process Water Computerized Control of Filtration, Deposit Control, and Purification***See Section A-8 of catalog (home page) for Additional Technical Information*

MODEL NUMBER	VOLUME:	HP	GPM	PRODUCT DIMENSIONS	APPROX SHIP WEIGHT
Low Pressure Systems (IN GALLONS)					
TWT-CTP-185-(HO)	0-2500	1.0	35	***	TBD
TWT-CTP-245-(HO)	2500-4000	2.0	63	***	TBD
TWT-CTP-305-(HO)	4000-6000	2.0	98**	***	TBD
High Pressure Systems					
TWT-CTP-365-(HP)	6000-9000	3.0	142**	***	TBD
TWT-CTP-425-(HP)	9000-13,000	5.0	192**	***	TBD
TWT-CTP-485-(HP)	13,000-16,000	5.0	252**	***	TBD
TWT-CTP-665-(HP)	16,000-30,000	7.5	474**	***	TBD
TWT-CTP-725-(HP)	30,000-36,000*	10.0	566**	***	TBD

*36,000-85,000 gallon systems prices upon request.

** Custom System Quote: Industry specific fluid treatment needs and upgrades

Custom Installation: Pricing to be established based upon proposal submitted at time of sale based on materials cost at time of purchase

NOTES: For facilities with multiple treatment needs and applications, contact TWT for specific installation and special pricing guidelines**Pricing case by case, must take into consideration:**

- Shipping/Handling/Insurance • Installation/Cost (time frame)
- Additional equipment needs (reinstallation)
- Any additional charges (redistribution point) • Consulting time, etc.

*** Custom built according to customer system application and GPM requirements.

Size and weight to be determined at time of purchase

TBD: Carriers shipping and handling costs for products are constantly changing. For that reason, it is difficult for TWT to determine the exact shipping method and weight for products before TWT has a confirmed and accepted purchase order in-house.



CUSTOM ENGINEERED & INTEGRATED (Fork Lift Skid-Mounted) HIGH VOLUME FLUID TREATMENT SYSTEMS (For potable, process and/or waste water applications)

TWT® PATENTED DEPOSIT CONTROL TECHNOLOGY • UV DISINFECTION/PURIFICATION

See Section B-3 of catalog (home page) for Additional Technical Information

ITEM NUMBER & PRODUCT DESCRIPTION:

PRODUCT DIMENSIONS

APPROX SHIP WEIGHT

TWT-CSMS-G2T-404-5007 400/600 GPM Treatment System *

TBD

#1 Transportable Fork Lift St/St Skid-Mounted System

Unit Dimensions Approximate: 48" W x 65" D x 55" H


400/600 (GPM) UV Disinfection/Purification Treatment System

- One (1) TWT-5C8-404 Deposit Control System
- Two (2) TWT-UV-5007 Disinfection/Purification Systems

Efficiency:

Expected 3 Log Reduction (99.9) for processing & drinking water

Expected 1-2 Log Reduction for wastewater applications



TWT-CSMS-G4T-406-5007 700/1200 GPM Treatment System *

TBD

#2 Transportable Fork Lift St/St Skid-Mounted System

Unit Dimensions Approximate: 48" W x 65" D x 55" H


700/1200 (GPM) UV Disinfection/Purification Treatment System

- One (1) TWT-5C8-406 Deposit Control System
- Four (4) TWT-UV-5007 Disinfection/Purification Systems

Efficiency:

Expected 3 Log Reduction (99.9) for processing & drinking water

Expected 1-2 Log Reduction for wastewater applications



TWT-CSMS-G6T-408-5007 1300/1500 GPM Treatment System *

TBD

#3 Transportable Fork Lift St/St Skid-Mounted System

Unit Dimensions Approximate: 48" W x 65" D x 75" H


1300/1500 (GPM) UV Disinfection/Purification Treatment System

- One (1) TWT-5C8-408 Deposit Control System
- Six (6) TWT-UV-5007 Disinfection/Purification Systems

Efficiency:

Expected 3 Log Reduction (99.9) for processing & drinking water

Expected 1-2 Log Reduction for wastewater applications



*Custom built according to customer system application and GPM requirements. Size and weight to be determined at time of purchase

Note:

Above systems are fully integrated and factory assembled.

Custom Orders: Larger pipe size (GPM) applications available upon request

TWT Inc. recommends that an initial supply of replacement products e.g., UV lamps etc. be stored at owners facility at all times, that will insure uninterrupted service and treatment. Review product list for replacement filters and ultra-violet lamps.

Upgrades: Customized TWT® systems to meet your treatment applications available upon request

TBD: Carriers shipping and handling costs for products are constantly changing. For that reason, it is difficult for TWT to determine the exact shipping method and weight for products before TWT has a confirmed and accepted purchase order in-house.

Components for High Volume Fluid Treatment System. Not to scale for reference only

