## Triangular Wave Technologies Enhanced Control Pool & Spa Management System



## Sparkling Clear Algae-Free Water Without Chemicals

## TECHNICAL DATA

Model # TWT-5C8-401

Height Width Depth Voltage Amperage Signal Frequency Pipe Size Range Coil Lenth 6.25" 7.75" 3.75" 120 vac less than 2 Amp 2-7 KHz up to 2" 7" Coil Wire Guage UL 1007 AWG#20

TWT-5C8-278

1.0 AMP control unit (high volume application) Ionization/Disinfection System for the control of Algae/Bacteria.

HeightWidthdepthVoltageAmperageElectrode Size8.5"11.5"6.0"120 vac1.0up to 6-inch

Designed for pool sizes up to 80,000 gallons

TWT-IRC-02 / Industrial Reaction Chamber

Factory wrapped 2 inch PVC pipe solenoid for use with TWT-5C8-402 Microprocessor Deposit Control System.

TWT-IDK-0258457/ ID Electrode Installation Kit

3" Electrode /2" PVC Tee/2" Tee-Cap and Conduit • Normal Conductivity-TDS

Also in sizes 4", 6" and 8".

## Pool & Spa Applications

Pool and Spa Integrated Systems—Apply all the needed elements for maximum Pool and Spa management in one simple packaged solution. TWT lonGuard Purification, TWT Microprocessor Deposit Controller, and TWT Industrial Reaction Chamber units are combined to provide a start-to-finish answer to simplified pool and spa management. TWT solutions are scalable to fit the volume you need - ask us to specify the system that workbest for you!



FLUID MANAGEMENT SOLUTIONS